

www.genesysro.com

Membrane cleaning protocol Cleaning survey form

This document is designed to gather the appropriate information to allow Genesys International to design a suitable membrane cleaning protocol for the optimum removal of foulants and deposits.

Section 1: Pre-treatment

Briefly describe existing pre-treatment (filters/tanks/cartridge filters etc):

Section 2: Membrane Details

Element Manufacturer, Model and size:

No of pressure vessels in Stage 1:	
No of pressure vessels in Stage 2:	
No of elements per pressure vessel:	
Can the stages be separated for cleaning?	

Section 3: CIP Details:

Cleaning tank volume:

Can CIP tank be heated?:

Filtration system installed in cleaning circuit:

Flux/pressure of recirculation pump:

Is there a suitable supply of permeate for flushing and preparing CIP solutions, please describe:

Contact Details:

Name:

Company:

Telephone:

Email:

Site Reference:

Section 4: Current Cleaning Regime:

Cleaning Frequency:

Membrane Replacement frequency:

Chemicals used and corresponding volumes:

pH and temperature:

Recirculation/soak times:

Flow rates and pressures:

Design parameters – permeate flow, permeate quality and dP:

Effectiveness – recovery of permeate flow/quality and dP after CIP:

Submit

Genesys International Limited 3A Aston Way, Middlewich, Cheshire, UK, CW10 0HS t: +44(0)1606 837 605 f: +44(0)1606 837 558 e: info@genesysro.com